

## Product Change Notice (PCN)

Date: **January 30th, 2026**

PCN Number: **PCN-0420187R-01**

### To Our Customers:

We appreciate your use of our products. Our commitment in maintaining and improving processes is demonstrated by plans to enhance our product quality, reliability, and manufacturability. The purpose of this notice is to inform you of a product change.

Product(s) Affected: **HSB26-343408**

Reason(s) for Change: *Factory Location Change*

Description of Change: *Product re-engineered for improved manufacturability and production yield. See image below for product changes. Cosmetic differences may be visible and not affect the form fit and function of the product.*

PREVIOUS SAME SKY DETAIL / IMAGE					NEW SAME SKY DETAIL / IMAGE																																																													
MODEL		thermal resistance <sup>1</sup>			power dissipation <sup>1</sup>			power dissipation <sup>1</sup>																																																										
		@ 75°C ΔT, net conv (°C/W)	@ 1W, net conv (°C/W)	@ 1W, 250 LFM (°C/W)	@ 1W, 400 LFM (°C/W)	@ 75°C ΔT, net conv (W)	@ 1W, net conv (W)	@ 1W, 250 LFM (W)	@ 1W, 400 LFM (W)																																																									
HSB26-343408		15.19	17.9	5.3	3.2	4.94	15.34	18.1	5.7	3.7	4.89																																																							
Note: 1. See performance curves for full thermal resistance details.																																																																		
PERFORMANCE CURVES																																																																		
<table border="1"> <thead> <tr> <th colspan="4">Heatsink Temperature Rise Above Ambient (ΔT + Ths - Ta) (°C)</th> </tr> <tr> <th>Power (W)</th> <th>Natural Conv.</th> <th>200 LFM</th> <th>400 LFM</th> </tr> </thead> <tbody> <tr><td>0</td><td>0</td><td>0</td><td>0</td></tr> <tr><td>1</td><td>17.9</td><td>5.3</td><td>3.2</td></tr> <tr><td>2</td><td>34.7</td><td>10.5</td><td>8.3</td></tr> <tr><td>3</td><td>49.9</td><td>15.6</td><td>9.4</td></tr> <tr><td>4</td><td>63.8</td><td>20.9</td><td>12.8</td></tr> <tr><td>5</td><td>76.0</td><td>25.2</td><td>15.9</td></tr> <tr><td>6</td><td>88.1</td><td>31.7</td><td>19.1</td></tr> <tr><td>7</td><td>100.1</td><td>38.9</td><td>22.5</td></tr> <tr><td>8</td><td>110.8</td><td>42.3</td><td>25.7</td></tr> <tr><td>9</td><td>121.1</td><td>47.6</td><td>29.1</td></tr> <tr><td>10</td><td>130.8</td><td>53.5</td><td>32.8</td></tr> </tbody> </table>										Heatsink Temperature Rise Above Ambient (ΔT + Ths - Ta) (°C)				Power (W)	Natural Conv.	200 LFM	400 LFM	0	0	0	0	1	17.9	5.3	3.2	2	34.7	10.5	8.3	3	49.9	15.6	9.4	4	63.8	20.9	12.8	5	76.0	25.2	15.9	6	88.1	31.7	19.1	7	100.1	38.9	22.5	8	110.8	42.3	25.7	9	121.1	47.6	29.1	10	130.8	53.5	32.8					
Heatsink Temperature Rise Above Ambient (ΔT + Ths - Ta) (°C)																																																																		
Power (W)	Natural Conv.	200 LFM	400 LFM																																																															
0	0	0	0																																																															
1	17.9	5.3	3.2																																																															
2	34.7	10.5	8.3																																																															
3	49.9	15.6	9.4																																																															
4	63.8	20.9	12.8																																																															
5	76.0	25.2	15.9																																																															
6	88.1	31.7	19.1																																																															
7	100.1	38.9	22.5																																																															
8	110.8	42.3	25.7																																																															
9	121.1	47.6	29.1																																																															
10	130.8	53.5	32.8																																																															
<small>The "hot spot" temperature measured on the heatsink Ta ambient temperature</small>					<table border="1"> <thead> <tr> <th colspan="4">Heatsink Temperature Rise Above Ambient (ΔT + Ths - Ta) (°C)</th> </tr> <tr> <th>Power (W)</th> <th>Natural Conv.</th> <th>200 LFM</th> <th>400 LFM</th> </tr> </thead> <tbody> <tr><td>0</td><td>0</td><td>0</td><td>0</td></tr> <tr><td>1</td><td>18.1</td><td>5.7</td><td>3.7</td></tr> <tr><td>2</td><td>34.8</td><td>11.1</td><td>7.1</td></tr> <tr><td>3</td><td>49.5</td><td>16.8</td><td>10.5</td></tr> <tr><td>4</td><td>63.9</td><td>22.7</td><td>14.1</td></tr> <tr><td>5</td><td>77.7</td><td>28.4</td><td>18.1</td></tr> <tr><td>6</td><td>90.3</td><td>34.3</td><td>21.8</td></tr> <tr><td>7</td><td>102.0</td><td>40.0</td><td>25.4</td></tr> <tr><td>8</td><td>114.6</td><td>45.7</td><td>29.2</td></tr> <tr><td>9</td><td>126.3</td><td>51.5</td><td>33.1</td></tr> <tr><td>10</td><td>138.7</td><td>57.4</td><td>36.8</td></tr> </tbody> </table>										Heatsink Temperature Rise Above Ambient (ΔT + Ths - Ta) (°C)				Power (W)	Natural Conv.	200 LFM	400 LFM	0	0	0	0	1	18.1	5.7	3.7	2	34.8	11.1	7.1	3	49.5	16.8	10.5	4	63.9	22.7	14.1	5	77.7	28.4	18.1	6	90.3	34.3	21.8	7	102.0	40.0	25.4	8	114.6	45.7	29.2	9	126.3	51.5	33.1	10	138.7	57.4	36.8
Heatsink Temperature Rise Above Ambient (ΔT + Ths - Ta) (°C)																																																																		
Power (W)	Natural Conv.	200 LFM	400 LFM																																																															
0	0	0	0																																																															
1	18.1	5.7	3.7																																																															
2	34.8	11.1	7.1																																																															
3	49.5	16.8	10.5																																																															
4	63.9	22.7	14.1																																																															
5	77.7	28.4	18.1																																																															
6	90.3	34.3	21.8																																																															
7	102.0	40.0	25.4																																																															
8	114.6	45.7	29.2																																																															
9	126.3	51.5	33.1																																																															
10	138.7	57.4	36.8																																																															
Weight: 15.6 g					Weight: 15.6 g																																																													

Affected Date Code: **1/30/2026**

Product Availability: *Pertaining to market availability*

PCN Approval:

Operations/Quality



Product Management

Handwritten initials "DH" in black ink, with a horizontal line extending to the right below them.

---

F-723-001

Revision: A

6405 SW Rosewood St, Ste C | Lake Oswego, OR 97035 | [sameskydevices.com](http://sameskydevices.com) | 877.323.3576