



# Product Change Notice (PCN)

Date: February 13th, 2026

PCN Number: PCN-0420230R-01

To Our Customers:

We appreciate your use of our products. Our commitment in maintaining and improving processes is demonstrated by plans to enhance our product quality, reliability, and manufacturability. The purpose of this notice is to inform you of a product change.

Product(s) Affected: *HSB31-212105*

Reason(s) for Change: *Factory Location Change*

Description of Change: *Product re-engineered for improved manufacturability and production yield. See image below for product changes. Cosmetic differences may be visible and not affect the form fit and function of the product.*

PREVIOUS SAME SKY DETAIL / IMAGE						NEW SAME SKY DETAIL / IMAGE																																																																			
<b>MODEL</b>						<b>MODEL</b>																																																																			
<table border="1"> <thead> <tr> <th rowspan="2"></th> <th colspan="4">thermal resistance<sup>1</sup></th> <th rowspan="2">power dissipation<sup>1</sup> @ 75°C ΔT, nat conv (W)</th> </tr> <tr> <th>@ 75°C ΔT, nat conv (°C/W)</th> <th>@ 1 W, nat conv (°C/W)</th> <th>@ 1 W, 200 LFM (°C/W)</th> <th>@ 1 W, 400 LFM (°C/W)</th> </tr> </thead> <tbody> <tr> <td>HSB31-212105</td> <td>29.33</td> <td>28.5</td> <td>9.9</td> <td>8.7</td> <td>2.98</td> </tr> </tbody> </table>							thermal resistance <sup>1</sup>				power dissipation <sup>1</sup> @ 75°C ΔT, nat conv (W)	@ 75°C ΔT, nat conv (°C/W)	@ 1 W, nat conv (°C/W)	@ 1 W, 200 LFM (°C/W)	@ 1 W, 400 LFM (°C/W)	HSB31-212105	29.33	28.5	9.9	8.7	2.98	<table border="1"> <thead> <tr> <th rowspan="2"></th> <th colspan="4">thermal resistance<sup>1</sup></th> <th rowspan="2">power dissipation<sup>1</sup> @ 75°C ΔT, nat conv (W)</th> </tr> <tr> <th>@ 75°C ΔT, nat conv (°C/W)</th> <th>@ 1 W, nat conv (°C/W)</th> <th>@ 1 W, 200 LFM (°C/W)</th> <th>@ 1 W, 400 LFM (°C/W)</th> </tr> </thead> <tbody> <tr> <td>HSB31-212105</td> <td>29.36</td> <td>33.9</td> <td>11.8</td> <td>7.6</td> <td>2.55</td> </tr> </tbody> </table>							thermal resistance <sup>1</sup>				power dissipation <sup>1</sup> @ 75°C ΔT, nat conv (W)	@ 75°C ΔT, nat conv (°C/W)	@ 1 W, nat conv (°C/W)	@ 1 W, 200 LFM (°C/W)	@ 1 W, 400 LFM (°C/W)	HSB31-212105	29.36	33.9	11.8	7.6	2.55																														
	thermal resistance <sup>1</sup>				power dissipation <sup>1</sup> @ 75°C ΔT, nat conv (W)																																																																				
	@ 75°C ΔT, nat conv (°C/W)	@ 1 W, nat conv (°C/W)	@ 1 W, 200 LFM (°C/W)	@ 1 W, 400 LFM (°C/W)																																																																					
HSB31-212105	29.33	28.5	9.9	8.7	2.98																																																																				
	thermal resistance <sup>1</sup>				power dissipation <sup>1</sup> @ 75°C ΔT, nat conv (W)																																																																				
	@ 75°C ΔT, nat conv (°C/W)	@ 1 W, nat conv (°C/W)	@ 1 W, 200 LFM (°C/W)	@ 1 W, 400 LFM (°C/W)																																																																					
HSB31-212105	29.36	33.9	11.8	7.6	2.55																																																																				
<p>Note: 1. See performance curves for full thermal resistance details.</p> <p><b>PERFORMANCE CURVES</b></p> <table border="1"> <thead> <tr> <th rowspan="2">Power (W)</th> <th colspan="3">Heatsink Temperature Rise Above Ambient (ΔT = T<sub>hs</sub> - T<sub>a</sub>) (°C)</th> </tr> <tr> <th>Natural Conv.</th> <th>200 LFM</th> <th>400 LFM</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td>1</td> <td>29.5</td> <td>9.9</td> <td>8.7</td> </tr> <tr> <td>2</td> <td>53.5</td> <td>20.0</td> <td>13.5</td> </tr> <tr> <td>3</td> <td>79.5</td> <td>29.9</td> <td>20.1</td> </tr> <tr> <td>4</td> <td>99.0</td> <td>39.8</td> <td>27.0</td> </tr> <tr> <td>5</td> <td>118.3</td> <td>49.6</td> <td>33.6</td> </tr> </tbody> </table>						Power (W)	Heatsink Temperature Rise Above Ambient (ΔT = T <sub>hs</sub> - T <sub>a</sub> ) (°C)			Natural Conv.	200 LFM	400 LFM	0	0	0	0	1	29.5	9.9	8.7	2	53.5	20.0	13.5	3	79.5	29.9	20.1	4	99.0	39.8	27.0	5	118.3	49.6	33.6	<p>Note: 1. See performance curves for full thermal resistance details.</p> <p><b>PERFORMANCE CURVES</b></p> <table border="1"> <thead> <tr> <th rowspan="2">Power (W)</th> <th colspan="3">Heatsink Temperature Rise Above Ambient (ΔT = T<sub>hs</sub> - T<sub>a</sub>) (°C)</th> </tr> <tr> <th>Natural Conv.</th> <th>200 LFM</th> <th>400 LFM</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td>1</td> <td>33.9</td> <td>11.8</td> <td>7.6</td> </tr> <tr> <td>2</td> <td>61.0</td> <td>23.2</td> <td>15.0</td> </tr> <tr> <td>3</td> <td>85.9</td> <td>35.0</td> <td>22.8</td> </tr> <tr> <td>4</td> <td>108.9</td> <td>47.1</td> <td>30.4</td> </tr> <tr> <td>5</td> <td>130.5</td> <td>58.9</td> <td>37.9</td> </tr> </tbody> </table>						Power (W)	Heatsink Temperature Rise Above Ambient (ΔT = T <sub>hs</sub> - T <sub>a</sub> ) (°C)			Natural Conv.	200 LFM	400 LFM	0	0	0	0	1	33.9	11.8	7.6	2	61.0	23.2	15.0	3	85.9	35.0	22.8	4	108.9	47.1	30.4	5	130.5	58.9	37.9
Power (W)	Heatsink Temperature Rise Above Ambient (ΔT = T <sub>hs</sub> - T <sub>a</sub> ) (°C)																																																																								
	Natural Conv.	200 LFM	400 LFM																																																																						
0	0	0	0																																																																						
1	29.5	9.9	8.7																																																																						
2	53.5	20.0	13.5																																																																						
3	79.5	29.9	20.1																																																																						
4	99.0	39.8	27.0																																																																						
5	118.3	49.6	33.6																																																																						
Power (W)	Heatsink Temperature Rise Above Ambient (ΔT = T <sub>hs</sub> - T <sub>a</sub> ) (°C)																																																																								
	Natural Conv.	200 LFM	400 LFM																																																																						
0	0	0	0																																																																						
1	33.9	11.8	7.6																																																																						
2	61.0	23.2	15.0																																																																						
3	85.9	35.0	22.8																																																																						
4	108.9	47.1	30.4																																																																						
5	130.5	58.9	37.9																																																																						

Affected Date Code: *2/13/2026*

Product Availability: *Pertaining to market availability*

PCN Approval:

Operations/Quality

Product Management

F-723-001

Revision: A

