

## Product Change Notice (PCN)

Date: **06/18/2026**

PCN Number: **PCN-0450679R-01**

To Our Customers:

We appreciate your use of our products. Our commitment in maintaining and improving processes is demonstrated by plans to enhance our product quality, reliability, and manufacturability. The purpose of this notice is to inform you of a product change.

Product(s) Affected: **RCJ-04X**

Reason(s) for Change: **Factory Location Change.**

Description of Change: **Mechanical, material and electrical differences as shown in the detail image below.**

PREVIOUS SAME SKY DETAIL / IMAGE	NEW SAME SKY DETAIL / IMAGE																																																																																										
<p><b>SPECIFICATIONS</b></p> <table border="1"> <thead> <tr> <th>parameter</th> <th>conditions/description</th> <th>min</th> <th>typ</th> <th>max</th> <th>units</th> </tr> </thead> <tbody> <tr> <td>contact resistance</td> <td></td> <td></td> <td></td> <td>30</td> <td>mΩ</td> </tr> <tr> <td>insulation resistance</td> <td>at 500 Vdc</td> <td>100</td> <td></td> <td></td> <td>MΩ</td> </tr> <tr> <td>voltage withstand</td> <td>for 1 minute</td> <td></td> <td></td> <td>500</td> <td>Vac</td> </tr> <tr> <td>life</td> <td></td> <td></td> <td>5,000</td> <td></td> <td>cycles</td> </tr> <tr> <td>flammability rating</td> <td>UL94V-0</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>RoHS</td> <td>yes</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	parameter	conditions/description	min	typ	max	units	contact resistance				30	mΩ	insulation resistance	at 500 Vdc	100			MΩ	voltage withstand	for 1 minute			500	Vac	life			5,000		cycles	flammability rating	UL94V-0					RoHS	yes					<p><b>SPECIFICATIONS</b></p> <table border="1"> <thead> <tr> <th>parameter</th> <th>conditions/description</th> <th>min</th> <th>typ</th> <th>max</th> <th>units</th> </tr> </thead> <tbody> <tr> <td>contact resistance</td> <td></td> <td></td> <td></td> <td>30</td> <td>mΩ</td> </tr> <tr> <td>insulation resistance</td> <td>at 500 Vdc</td> <td>100</td> <td></td> <td></td> <td>MΩ</td> </tr> <tr> <td>voltage withstand</td> <td>for 1 minute</td> <td></td> <td></td> <td>500</td> <td>Vac</td> </tr> <tr> <td>operating temperature</td> <td></td> <td>-25</td> <td></td> <td>70</td> <td>°C</td> </tr> <tr> <td>life</td> <td></td> <td></td> <td>5,000</td> <td></td> <td>cycles</td> </tr> <tr> <td>flammability rating</td> <td>UL94V-0</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>RoHS</td> <td>yes</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	parameter	conditions/description	min	typ	max	units	contact resistance				30	mΩ	insulation resistance	at 500 Vdc	100			MΩ	voltage withstand	for 1 minute			500	Vac	operating temperature		-25		70	°C	life			5,000		cycles	flammability rating	UL94V-0					RoHS	yes				
parameter	conditions/description	min	typ	max	units																																																																																						
contact resistance				30	mΩ																																																																																						
insulation resistance	at 500 Vdc	100			MΩ																																																																																						
voltage withstand	for 1 minute			500	Vac																																																																																						
life			5,000		cycles																																																																																						
flammability rating	UL94V-0																																																																																										
RoHS	yes																																																																																										
parameter	conditions/description	min	typ	max	units																																																																																						
contact resistance				30	mΩ																																																																																						
insulation resistance	at 500 Vdc	100			MΩ																																																																																						
voltage withstand	for 1 minute			500	Vac																																																																																						
operating temperature		-25		70	°C																																																																																						
life			5,000		cycles																																																																																						
flammability rating	UL94V-0																																																																																										
RoHS	yes																																																																																										

Affected Date Code: **All orders placed after 06/11/2026**

PCN Approval:

F-723-001

Revision: A



Operations/Quality

A handwritten signature in black ink, appearing to read 'Robert Davis', is written over a horizontal line.

Product Management

A handwritten signature in black ink is written over a horizontal line. The signature is stylized and difficult to decipher.