

PREVIOUS CUI DETAIL / IMAGE				NEW CUI DEVICES DETAIL / IMAGE																																																															
<table border="1"> <thead> <tr> <th>DESCRIPTION</th> <th>MATERIAL</th> <th>PLATING/COLOR</th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>terminal 1</td> <td>stainless steel</td> <td>silver</td> <td></td> <td></td> <td></td> </tr> <tr> <td>terminal 2</td> <td>copper alloy</td> <td>silver</td> <td></td> <td></td> <td></td> </tr> <tr> <td>terminal 3</td> <td>copper alloy</td> <td>silver</td> <td></td> <td></td> <td></td> </tr> <tr> <td>housing</td> <td>PA8T (UL94V-D)</td> <td>black</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>				DESCRIPTION	MATERIAL	PLATING/COLOR				terminal 1	stainless steel	silver				terminal 2	copper alloy	silver				terminal 3	copper alloy	silver				housing	PA8T (UL94V-D)	black				<table border="1"> <thead> <tr> <th>DESCRIPTION</th> <th>MATERIAL</th> <th>PLATING/COLOR</th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>terminal 1</td> <td>stainless steel</td> <td>silver over nickel</td> <td></td> <td></td> <td></td> </tr> <tr> <td>terminal 2</td> <td>copper alloy</td> <td>silver over nickel</td> <td></td> <td></td> <td></td> </tr> <tr> <td>terminal 3</td> <td>copper alloy</td> <td>silver over nickel</td> <td></td> <td></td> <td></td> </tr> <tr> <td>housing</td> <td>PA10T (UL94V-D)</td> <td>black</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>				DESCRIPTION	MATERIAL	PLATING/COLOR				terminal 1	stainless steel	silver over nickel				terminal 2	copper alloy	silver over nickel				terminal 3	copper alloy	silver over nickel				housing	PA10T (UL94V-D)	black			
DESCRIPTION	MATERIAL	PLATING/COLOR																																																																	
terminal 1	stainless steel	silver																																																																	
terminal 2	copper alloy	silver																																																																	
terminal 3	copper alloy	silver																																																																	
housing	PA8T (UL94V-D)	black																																																																	
DESCRIPTION	MATERIAL	PLATING/COLOR																																																																	
terminal 1	stainless steel	silver over nickel																																																																	
terminal 2	copper alloy	silver over nickel																																																																	
terminal 3	copper alloy	silver over nickel																																																																	
housing	PA10T (UL94V-D)	black																																																																	
<p>SOLDERABILITY</p> <table border="1"> <thead> <tr> <th>parameter</th> <th>conditions/description</th> <th>min</th> <th>typ</th> <th>max</th> <th>units</th> </tr> </thead> <tbody> <tr> <td>refl storage¹</td> <td>10-30°C, <10% humidity</td> <td></td> <td></td> <td></td> <td>°C</td> </tr> <tr> <td>reflow soldering²</td> <td>see reflow profile</td> <td>255</td> <td>260</td> <td></td> <td>°C</td> </tr> <tr> <td>drying conditions³</td> <td>parts in reel: bake at 110°C for 4 hours parts removed from reel: bake at 110°C for 4 hours</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table> <p>Notes: 1. CUI Devices recommends to solder within 72 hours from opening vacuum packaging at a temperature <30°C & relative humidity <65%. 2. It is recommended to reflow solder within 72 hours from opening vacuum packaging at a temperature <30°C & relative humidity <65%. 3. When exceeding floor life by >72 hours.</p>				parameter	conditions/description	min	typ	max	units	refl storage ¹	10-30°C, <10% humidity				°C	reflow soldering ²	see reflow profile	255	260		°C	drying conditions ³	parts in reel: bake at 110°C for 4 hours parts removed from reel: bake at 110°C for 4 hours					<p>SOLDERABILITY</p> <table border="1"> <thead> <tr> <th>parameter</th> <th>conditions/description</th> <th>min</th> <th>typ</th> <th>max</th> <th>units</th> </tr> </thead> <tbody> <tr> <td>refl storage¹</td> <td>at relative humidity <60%</td> <td></td> <td></td> <td>40</td> <td>°C</td> </tr> <tr> <td>reflow soldering²</td> <td>see reflow profile</td> <td>255</td> <td>260</td> <td>265</td> <td>°C</td> </tr> <tr> <td>drying conditions³</td> <td>parts in reel: bake at 40°C ±5°C for 72 hours parts removed from reel: bake at 40°C ±5°C for 10 hours</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table> <p>Notes: 1. It is recommended to reflow solder within 72 hours from opening vacuum packaging at a temperature <30°C & relative humidity <65%. 2. When exceeding floor life by >72 hours.</p>				parameter	conditions/description	min	typ	max	units	refl storage ¹	at relative humidity <60%			40	°C	reflow soldering ²	see reflow profile	255	260	265	°C	drying conditions ³	parts in reel: bake at 40°C ±5°C for 72 hours parts removed from reel: bake at 40°C ±5°C for 10 hours																
parameter	conditions/description	min	typ	max	units																																																														
refl storage ¹	10-30°C, <10% humidity				°C																																																														
reflow soldering ²	see reflow profile	255	260		°C																																																														
drying conditions ³	parts in reel: bake at 110°C for 4 hours parts removed from reel: bake at 110°C for 4 hours																																																																		
parameter	conditions/description	min	typ	max	units																																																														
refl storage ¹	at relative humidity <60%			40	°C																																																														
reflow soldering ²	see reflow profile	255	260	265	°C																																																														
drying conditions ³	parts in reel: bake at 40°C ±5°C for 72 hours parts removed from reel: bake at 40°C ±5°C for 10 hours																																																																		

PREVIOUS CUI DETAIL / IMAGE		NEW CUI DEVICES DETAIL / IMAGE	
<p>PACKAGING</p> <p>units: mm Reel Size: Ø330 mm Reel QTY: 1,000 pcs per reel</p>		<p>PACKAGING</p> <p>units: mm Reel Size: Ø330 mm Reel QTY: 1,000 pcs per reel</p>	

Affected Date Code: All orders placed before **10/25/2024** will be pre-PCN parts. Orders placed after **10/25/2024** will be manufactured in accordance with the PCN. Please check updated 2D drawing on or after **10/25/2024**.

PCN Approval:

Operations/Quality

Product Management