

**MODEL:** PJ-105BH-MSMT-TR | **DESCRIPTION:** DC POWER JACK**FEATURES**


- 2.5 mm center pin
- reflow solder
- tape & reel packaging

**SPECIFICATIONS**

parameter	conditions/description	min	typ	max	units
rated input voltage			20		Vdc
rated input current				12	A
contact resistance				30	mΩ
insulation resistance	at 500 Vdc	100			MΩ
voltage withstand	for 1 minute			500	Vac
insertion/withdrawal force		1		3	kg
operating temperature		-20		70	°C
storage temperature		-40		85	°C
life			10,000		cycles
flammability rating	UL94V-0				
RoHS	yes				


SOLDERABILITY

parameter	conditions/description	min	typ	max	units
reel storage	5~35°C, <75% humidity				°C
reflow soldering	see reflow profile			260	°C
drying conditions	bake at 120°C for 4 hours				




MECHANICAL DRAWING


units: mm
tolerance:
X.X: ±0.38 mm
X.XX ±0.30 mm
X.XXX: ±0.15 mm
PCB: ±0.05 mm
unless otherwise specified
PCB thickness: 1.3 mm



ITEM	DESCRIPTION	MATERIAL	PLATING/COLOR
1	housing	LCP [UL94V-0]	black
2	terminal 1	brass	gold flash over nickel
3	terminal 2	C5210-EH t=0.30	gold flash
4	terminal 3	C2680-H t=0.30	gold flash
5	ground	SUS301-H t=0.10	---
6	shield	C2680-H t=0.35	1 μm nickel



Recommended PCB Layout
Top View



MATING PLUG
Jack Insertion Depth: 8.2 mm

Schematic	
Model	PJ-105BH-MSMT-TR
Center Pin	Ø2.5 mm

.....
sameskydevices.com

REVISION HISTORY

rev.	description	date
1.0	initial release	09/23/2024

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

sameskydevices.com