


**SERIES:** DS06-127-SMT | **DESCRIPTION:** DIP SWITCH**FEATURES**

- 1.27 pitch
- tape and reel
- long and short pins

**SPECIFICATIONS**

parameter	conditions/description	min	typ	max	units
rated voltage (per pole)	switching non-switching			24 50	Vdc Vdc
rated current (per pole)	switching non-switching			25 100	mA mA
withstanding voltage	for 1 minute		300		Vac
contact resistance	initial after life test			100 200	mΩ mΩ
insulation resistance	at 100 Vdc	100			MΩ
operating force				800	g
operating temperature		-20		85	°C
storage temperature		-40		85	°C
life		2000			cycles
flammability rating	UL94V-0				
RoHS	yes				

PART NUMBER KEY**DS06 - 127 - XX - XX BK - SMT - TR**


Base Number

Pin Length:
1S = Short Pins
1L = Long PinsNo. of Poles:
02 06
04 08

MECHANICAL DRAWING

units: mm
tolerance:
0.0<X≤6.0: ±0.05 mm
6.0<X≤30.0: ±0.08 mm
30.0<X≤53.0: ±0.12 mm
53.0<X≤70.0: ±0.15 mm
70.0<X≤90.0: ±0.20 mm
90.0<X≤115.0: ±0.25 mm
X>140.0: ±0.30 mm
unless otherwise noted

ITEM	DESCRIPTION	MATERIAL	PLATING/COLOR
1	actuator	PA9T [UL94V-0]	white
2	housing 1	PA9T [UL94V-0]	black
3	spring	steel	---
4	housing 2	PA9T [UL94V-0]	black
5	pin 1	copper alloy	gold
6	pin 2	copper alloy	gold




Recommended PCB Layout
Top View

This series is constructed of single piece modules where L is the total length, P is the pitch, and N is the number of poles.				
N	02	04	06	08
L	3.68	6.22	8.76	11.30
B	1.27	3.81	6.35	8.89

SOLDERABILITY






parameter	conditions/description	min	typ	max	units
hand soldering ¹	for maximum 3 seconds	315	320	325	°C
reflow soldering ¹	240-260 °C (20 seconds max)			260	°C

Notes: 1. Keep in "off" position during soldering.



PACKAGING

units: mm

Reel Size: $\varnothing 330$ mm
Reel QTY: 800 PCS**2 Pole Models****4 Pole Models****6 Pole Models****8 Pole Models**

REVISION HISTORY

rev.	description	date
1.0	initial release	09/09/2026

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

sameskydevices.com