


**MODEL:** CPT-14146-80T | **DESCRIPTION:** PIEZO BUZZER TRANSDUCER**FEATURES**

- 30 Vp-p max operating voltage
- 80 dB

**SPECIFICATIONS**

| parameter                 | conditions/description                                                            | min   | typ   | max    | units |
|---------------------------|-----------------------------------------------------------------------------------|-------|-------|--------|-------|
| rated voltage             |  |       | 10    |        | Vp-p  |
| operating voltage         |                                                                                   |       |       | 30     | Vp-p  |
| current consumption       | at 10 Vp-p, 4,000 Hz, ½ duty square wave                                          |       |       | 7      | mA    |
| rated frequency           |                                                                                   |       | 4,000 |        | Hz    |
| sound pressure level      | at 10 cm, 10 Vp-p, 4,000 Hz, square wave                                          | 80    |       |        | dB    |
| electrostatic capacitance | at 120 Hz / 1 V                                                                   | 5,950 | 8,500 | 11,050 | pF    |
| dimensions                | Ø14 x 6.7                                                                         |       |       |        | mm    |
| weight                    |                                                                                   |       |       | 1.0    | g     |
| material                  | PBT+10% GF                                                                        |       |       |        |       |
| terminal                  | pin (gold plating)                                                                |       |       |        |       |
| operating temperature     |                                                                                   | -30   |       | 85     | °C    |
| storage temperature       |                                                                                   | -40   |       | 90     | °C    |
| washable                  | no                                                                                |       |       |        |       |
| RoHS                      | yes                                                                               |       |       |        |       |


Notes: 1. All specifications measured at 5-35°C, humidity at 45-85%, under 86-106 kPa pressure, unless otherwise noted.

**SOLDERABILITY**


| parameter      | conditions/description | min | typ | max | units |
|----------------|------------------------|-----|-----|-----|-------|
| hand soldering | for 2 seconds          | 330 |     | 380 | °C    |

## MECHANICAL DRAWING

units: mm  
tolerance:  $\pm 0.5$  mm



## FREQUENCY RESPONSE CURVE




## APPLICATION CIRCUIT



PACKAGING


units: mm

Tray Size: 184 x 180 x 23 mm  
Carton Size: 440 x 400 x 310 mm  
Tray QTY: 100 pcs per tray  
Carton QTY: 6,000 pcs per carton



|               |                          |
|---------------|--------------------------|
| Lot No.       | XXXXXXXXXX               |
| Part No.      | XXXXXXXXXX<br>XXXXXXXXXX |
| Quantity.     | XXXX Pcs                 |
| Date:         | DD MM YY                 |
| MADE IN CHINA |                          |

RoHs Compliant



REVISION HISTORY

| rev. | description                       | date       |
|------|-----------------------------------|------------|
| 1.0  | initial release                   | 07/07/2021 |
| 1.01 | logo, datasheet style update      | 08/05/2022 |
| 1.02 | CUI Devices rebranded to Same Sky | 09/11/2024 |

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

**sameskydevices.com**