


**MODEL:** UJ32-C-V-G-SMT-TR | **DESCRIPTION:** USB RECEPTACLE**FEATURES**

- USB Type C receptacle
- USB 3.2 Gen 2x2
- 20 Gbit/s data transfer speed
- reflow solder compatible
- vertical mount
- tape & reel packaging

**SPECIFICATIONS**


parameter	conditions/description	min	typ	max	units
USB standard	USB 3.2 Gen 2x2				
rated input voltage				20	Vdc
rated input current	as per EIA-364-70, Method B				
	power pins collectively [A1, A4, A9, A12, B1, B4, B9, B12]			5.0	A
	VCONN pins individually [A5, B5]			1.25	A
	all other signal pins individually			0.25	A
contact resistance ¹	between terminals and mating plug			40	mΩ
insulation resistance	between adjacent contacts	100			MΩ
voltage withstand	between adjacent contacts	100			Vac
insertion force	at a rate of 12.5 mm/min	5		20	N
withdrawal force	at a rate of 12.5 mm/min	8		20	N
life	at a rate of 200 cycles per hour		10,000		cycles
operating temperature		-40		85	°C
flammability rating	UL94V-0				
RoHS	yes				

Note: 1. When measured at 20 mV / 100 mA.
2. All specifications measured at 10-35°C, humidity at 45-85%, under standard atmospheric pressure, unless otherwise noted.

SOLDERABILITY

parameter	conditions/description	min	typ	max	units
reel storage	at relative humidity 65~70%	25		30	°C
reflow soldering ³	see reflow profile		255	260	°C





Note: 3. It is recommended to reflow solder within 3 months from opening vacuum packaging at a temperature of 25-30°C & relative humidity 65-70%.






MECHANICAL DRAWING

units: mm
tolerance:
X. ± 0.50 mm
X.X ± 0.30 mm
X.XX ± 0.20 mm
X.XXX ± 0.10 mm
unless otherwise noted

	MATERIAL	PLATING
insulator	LCP [UL94V-0]	black
contact	copper alloy	contact area: gold flash solder area: matte tin over nickel
shell	stainless steel	nickel



MATING CONDITION



INCREASE THE DIAGRAMS OF CAP
SC 1:2

units: mm
PCB tolerance: ± 0.05 mm
PCB thickness: 1.2 mm

Technical drawing of a mechanical part, likely a bracket or plate, showing dimensions and tolerances. The drawing includes the following features and dimensions:

- Overall Dimensions:**
 - Width: 10.60
 - Height: 6.41
- Top Section:**
 - Top edge: 2-1.00, 2-0.60
 - Top-left corner: 2-0.25, 2-1.70, 2-1.20
 - Top-right corner: 2-1.06, 2-0.45, 2-0.43
- Bottom Section:**
 - Bottom edge: 2-0.60, 2-1.00
 - Bottom-left corner: 2-0.95, 2-1.25, 2-1.85
 - Bottom-right corner: 2-0.50, 2-0.60, 2-1.00
- Internal Features and Dimensions:**
 - Central horizontal slot: 2-0.80, 4.06, 5.50, 7.50, 7.70
 - Central vertical slot: 2-0.98, 2-1.45, 2-1.75
 - Central hole: 2-0.65
 - Top-left hole: 2-2.50, 2-1.90
 - Top-right hole: 2-1.75
 - Bottom-left hole: 2-0.60, 2-0.95
 - Bottom-right hole: 2-0.50, 2-0.60, 2-1.00
- Tolerances and Surface Finish:**
 - Surface finish: 24-0.30
 - Dimensional tolerance: ± 0.05 (indicated by a box around the tolerance value)
 - Surface finish: 2-0.05 (indicated by a box around the tolerance value)

sameskydevices.com

PACKAGING


units: mm

Reel Size: $\varnothing 330$ mm

Reel QTY: 150 pcs per reel

Carton Size: 350 x 350 x 470 mm

Carton QTY: 1,850 pcs



REVISION HISTORY

rev.	description	date
1.0	initial release	06/15/2022
1.01	logo, datasheet style update	08/05/2022
1.02	CUI Devices rebranded to Same Sky	09/12/2024

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

sameskydevices.com