

Additional Resources: Product Page

date 09/11/2024

page 1 of 3

MODEL: GC0201MAP-1 | DESCRIPTION: SPEAKER

- 20 mm round frame
- 8 Ω impedance
- rated 0.5 W
- neodymium magnet
- PET cone






SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
input power			0.5	1.0	W
impedance	at 1.2 kHz, 1 V	6.8	8	9.2	Ω
resonant frequency (Fo)	at Fo, 1 V	690	850	1,010	Hz
frequency response		Fo		10,000	Hz
sound pressure level	at 0.5 W, 50 cm, avg at 0.8, 1.0, 1.2, 1.5 kHz	79	82	85	dB
buzz, rattle, etc.	must be normal at sine wave, frequency range			2.0	V
dimensions	Ø20.0 x 3.2				mm
magnet	Nd-Fe-B				
cone material	PET				
terminal	solder pins			-	
weight		 	2.9		g
operating temperature		-25		60	°C
hand soldering	for maximum 3 seconds	340	350	360	°C
RoHS	yes				




MECHANICAL DRAWING

units: mm tolerance: ±0.5 mm



FREQUENCY RESPONSE CURVE

parameter	conditions/description					
potentiometer range	50 dB					
rectifier	RMS					
lower limit frequency	20 Hz					
wr. speed	100 mm/sec					
zero level	50.dB					



REVISION HISTORY

rev.	description	date	
1.0	initial release	05/21/2007	
1.01	brand update	01/28/2021	
1.02	logo, datasheet style update	08/05/2022	
1.03	CUI Devices rebranded to Same Sky	09/11/2024	

The revision history provided is for informational purposes only and is believed to be accurate.





Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.