

**SERIES:** CES-693118-34X | **DESCRIPTION:** SPEAKER**FEATURES**

- adhesive included
- mounting screw holes
- 300 Hz resonant frequency

**SPECIFICATIONS**

| parameter               | conditions/description                                    | min   | typ   | max    | units    |
|-------------------------|-----------------------------------------------------------|-------|-------|--------|----------|
| input power             | max power: 1 min. on, 2 min. off, 10 cycles               |       | 3.0   | 4.0    | W        |
| impedance               | at 1 kHz, 1 W                                             | 3.4   | 4.0   | 4.6    | $\Omega$ |
| resonant frequency (Fo) | at 1.0 W                                                  | 240   | 300   | 360    | Hz       |
| frequency response      |                                                           | Fo    |       | 13,000 | Hz       |
| sound pressure level    | at 1.0 W, 50 cm, avg at 0.8, 1.0, 4.0, 5.0 kHz            | 80    | 83    | 86     | dB       |
| distortion              | at 1.0 kHz, 1.0 W, 50 cm                                  |       |       | 10     | %        |
| buzz, rattle, etc.      | must be normal at sine wave between 300 Hz~3 kHz          |       |       | 3.46   | V        |
| polarity                | cone moves forward w/ positive dc current to "+" terminal |       |       |        |          |
| dimensions              | 69.6 x 31 x 17.9                                          |       |       |        | mm       |
| magnet                  | Nd-Fe-B                                                   |       |       |        |          |
| enclosure material      | ABS + PC                                                  |       |       |        |          |
| cone material           | PU + PET                                                  |       |       |        |          |
| weight                  | wire leads model                                          | 17.01 | 18.90 | 20.79  | g        |
|                         | wire leads with connector model                           | 17.06 | 18.95 | 20.85  | g        |
| operating temperature   |                                                           | -25   |       | 55     | °C       |
| storage temperature     |                                                           | -25   |       | 55     | °C       |
| hand soldering          | for 3~5 seconds (wire leads model only)                   | 370   | 380   | 390    | °C       |
| RoHS                    | yes                                                       |       |       |        |          |

Notes: 1. All specifications measured at 15~35°C, humidity at 25~75%, under 86~106 kPa pressure, unless otherwise noted.

**PART NUMBER KEY****CES - 693118 - 34 XX**

Base Number

Termination Options:


L200 = 200 mm wire leads

L200B = 200 mm wire leads with equivalent to Molex 51021-0200 connector

## MECHANICAL DRAWING (WIRE LEADS)

units: mm

wire: UL1571 30 AWG






## MECHANICAL DRAWING (WIRE LEADS W/ CONNECTOR)

units: mm

wire: UL1571 30 AWG


connector: Equivalent to Molex 51021-0200

mating connector: Molex 53261-0271 or equivalent




## RESPONSE CURVES

### Frequency Response Curve



### Total Harmonic Distortion Curve



REVISION HISTORY

| rev. | description     | date       |
|------|-----------------|------------|
| 1.0  | initial release | 09/14/2026 |

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

**sameskydevices.com**