CUI Devices is now Same Sky! Learn More

SERIES: SSK06-MPH-100 | DESCRIPTION: RECTANGULAR CONNECTOR

FEATURES

- male pin header
- 1.0 mm pitch
- straight pins
- double row
- gold flash

RoHS

SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
rated voltage				125	V
rated current				0.75	A
dielectric withstanding voltage	at 2 mA cut-off current for 1 minute		500		Vac
contact resistance	measured at 1 kHz AC, 100 mA			30	mΩ
insulation resistance	at 500 Vdc for 1 minute	1,000			MΩ
retention force	per pin	0.3			kgf
insertion force	per pin			0.18	kgf
withdrawal force	per pin	0.02			kgf
life			100		cycles
operating temperature		-40		105	°C
flammability rating	UL94V-0				
RoHS	yes				

SOLDERABILITY

parameter	conditions/description	min	typ	max	units
wave soldering	for 3±0.5 seconds	240	245	250	°C

PART NUMBER KEY

SSK06 - MPH - 100 - B XX

Base Number

No. of Pins:

2 = 2x2	12 = 2x12
3 = 2x3	13 = 2x13
4 = 2x4	14 = 2x14
5 = 2x5	15 = 2x15
6 = 2x6	16 = 2x16
7 = 2x7	17 = 2x17
8 = 2x8	18 = 2x18
9 = 2x9	19 = 2x19
10 = 2x10	20 = 2x20
11 = 2x11	

MECHANICAL DRAWING

units: mm
tolerance:
X.X ±0.30 mm
X.XX ±0.20 mm
X.XXX ±0.15 mm
unless otherwise noted

DESCRIPTION	MATERIAL	PLATING/COLOR
housing	PA6T (UL94V-0)	black
contacts	brass	0.2 µ" min gold flash over nickel







Recommended PCB Layout
Top View

This series is constructed of single piece modules where A & B are length dimensions and N is the number of poles.										
N	02	03	04	05	06	07	08	09	10	11
A	1.80	2.80	3.80	4.80	5.80	6.80	7.80	8.80	9.80	10.80
B	1.00	2.00	3.00	4.00	5.00	6.00	7.00	8.00	9.00	10.00
N	12	13	14	15	16	17	18	19	20	
A	11.80	12.80	13.80	14.80	15.80	16.80	17.80	18.80	19.80	
B	11.00	12.00	13.00	14.00	15.00	16.00	17.00	18.00	19.00	

REVISION HISTORY

rev.	description	date
1.0	initial release	10/22/2026

The revision history provided is for informational purposes only and is believed to be accurate.

Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.